

10W-40

It's tough out there and getting tougher for your commercial transport business. The world is changing at breakneck speed, throwing an ever-growing, intense set of external challenges and pressures your way. Yet, in the face of all this, you are relied upon to get the job done. The same is true of your truck.

Description and Applications

10W-40 is a synthetic engine oil engineered to stay stronger for longer, forming a uniquely strong fluid film to extend drain intervals and engine life, maximize performance and keep your business and your trucks moving. This helps in extending engine life and reduces the total cost of ownership.

10W-40 is suitable for all types of heavy-duty diesel applications including modern and high-output emission engines. It is also suitable for new and old turbocharged and naturally aspirated diesel engines, both on-highway and off-highway, running on high or ultra-low Sulphur diesel and bio-diesel.

Benefits

10W-40 enhances your Business Profits and your vehicle availability while significantly reducing your operating costs through:

- **Maintains oil at optimal viscosity levels, delivering optimal lubrication to prevent unplanned breakdowns.**
- **Longer Drain Interval and Engine Life** driven by:
 - o Excellent control in deposit build ups, delivering optimum fleet's engine performance
 - o Keeps the acidic level under control, preventing corrosion and increasing the durability and the life of your engine
 - o Outstanding protection with high anti-wear properties to protect engine in severe conditions.
 - o Longer oil drain capability, especially on low emission engines.

Provides outstanding Driving Experience through:

- **Effectively combats high concentration of soot build ups, critical to prevent loss of vehicle horsepower**
- **Excellent low temperature viscosity for improved lubrication during start-up**

Specifications and Recommendations

Specifications:

- API CI-4
- ACEA E4, E7

Meet requirements:

- DTFR 15B120 (MB 228.5)

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.870
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	14.5
Viscosity Index	ASTM D 2270	-	150
Flash Point COC	ASTM D 92	°C	>210
TBN	ASTM D 2896	mgKOH/g	12.5
CCS at -25°C	ASTM D5293	mPa·s (cP)	5500
Pour Point	ASTM D 97	°C	-42