

SAE 10W

Designed for wear protection and to control corrosion for older commercial vehicle diesel engines

Description and Applications

SAE 10W is a monograde diesel engine, formulated for commercial vehicle diesel engines, where API CF is recommended, to help control against wear and control corrosion.

SAE 10W is suitable for all types of older commercial vehicle diesel applications and high-revolution turbocharged diesel engines for both on-highway and off-highway.

Benefits

SAE 10W delivers:

- **Piston cleanliness & minimizing deposits build ups, protects engine from wear**
- **Helps dispersing soot, hence reduces soot induced oil thickening.**
- **Good TBN retention effectively neutralizing the acidic by-products from combustion.**

Specifications

Specifications:

- API CF

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0,895
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	5,2
Viscosity Index	ASTM D 2270	-	99
Flash Point COC	ASTM D 92	°C	> 210
TBN	ASTM D 2896	mgKOH/g	6
Pour Point	ASTM D 97	°C	-30